


CAC Technology® Data Sheet

RF Coaxial Cable P/N: 33P1_FEP

Description

33P1_FEP

the double shield of Tape&Braid flexible coaxial cable, high performance microwave cable.



Construction

Inner Conductor	① Silver Plated Copper	0.91mm ± 0.02
Dielectric	② LD PTFE	2.70mm
Outer Conductor	③ Silver Plated Copper Tape	2.90mm
Braiding	④ Silver Plated Copper Braid	3.30 ± 0.05
Jacket	⑤ FEP, Light Green	3.70 ± 0.10

Electrical Data


Impedance	50 ohm
Max. operating frequency	40 GHz
Velocity of signal propagation	76%
Shielding effectiveness	> 90 dB (@1 GHz)
Max. operating voltage	1600V

Mechanical Data

Weight	38g/ m	
Min. bending radius	static	18 mm
	dynamic	36mm

Environmental Data

Temperature range	-55 °C ~ +165 °C
2011/65/EU (RoHS)	compliant





Attenuation & CW Power

Frequency	Attenuation	Attenuation	CW Power
GHz	dB/100m	dB/100ft	W
1	38.12	11.62	503.37
3	67.93	20.70	282.48
5	89.38	27.24	214.67
7	107.39	32.73	178.68
9	123.36	37.60	155.55
11	137.95	42.05	139.09
13	151.53	46.19	126.63
15	164.33	50.09	116.77
17	176.48	53.79	108.72
19	188.12	57.34	102.00
21	199.31	60.75	96.27
23	210.12	64.04	91.32
25	220.60	67.24	86.98
27	230.78	70.34	83.14
29	240.70	73.37	79.72
31	250.39	76.32	76.63
33	259.86	79.21	73.84
35	269.14	82.03	71.29
37	278.25	84.81	68.96
39	287.19	87.53	66.81
40	291.60	88.88	65.80

Version	Drawn/Date	Check/Date
01	Jinyuan 2012.10.18	wangzhen 2012.10.19



proprietary information:
the information with this data sheet is proprietary
and shall not be used for disclosed without prior
written permission from CAC Technology

Hefei CAC Electronic Technology Co.,Ltd.
Tel: 0086-551-63718423
Fax:0086-551-63718413
www.cactechnology.com

